

GECO SERIES

OUTDOOR PRODUCTS MFW1H7D1 SIGNAGE LIGHT



The GECO MFW1H7D1 from Aeralux is a compact and low profile LED SIGNAGE LIGHT with a 170 degree beam angle. This enables these modules to be suitable for medium channel letters depth of more than 6 cm/2.4in. These also have great heat dissipation to ensure long life expectancy.

Project:

Oty:

Notes:

OPERATING & ELECTRICAL

PERFORMANCE

IP Rating

Input Voltage 12VDC Power factor 0.9

Total harmonic distortion (THD) <2

INSTALLATION Mounting metho

12VDC Mounting method Adhesive 3M tape

<20% WARRANTY

System warranty

5 years

Lumens per Watt 163 LPW at 80CRI @4000K

Power consumption 0.5W

Beam angle 170°

Power Supply Not included

Lumen maintenance Rated for 85% initial lumen output at 50,000 hours of operation, operated at 25°C ambient temperature; per guidelines published by the Illuminating

Engineering Society (IES). (L85 at 50,000 hours)


APPLICATION CONDITION

Ambient temperature range -25 to 60°C

IP68

ORDERING GUIDE

MFW1H7D1	-3
FIXTURE FAMILY	ССТ
MFW1H7D1 AERALUX compact signage LED 12V DC	-3 3000K CCT
	-4 4000K CCT
	-5 5000K CCT
	-6 6500K CCT



EXAMPLE: MFW1H7D1-3





Aeralux Incorporation All Rights Reserved. Any information provided is subject to change without notice. All values are typical values when measured under normal laboratory conditions.