Assembly Instruction Sheet #IS-1233W36-36 or Style 1233W36-36

Tools Required: Flathead screwdriver, Phillips screwdriver, pilers, dril X mm , dril Y mm drill bit. Light Source: (2) 120V LED *35W DIMMABLE (3000K+6000K)


Estimated Ass ribly Time: 10-20 minutes


Preparation: Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

$oldsymbol{\Delta}$ Warnings and Cautions

Turn off electricity at circuit breaker or main fuse box before Installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation.


Package Contents





1) Measure the Distance between the holes on the back of the mirror, then proceed to mark the wall to match. Ensure that the markings are aligned with the studs in the

1-1)Using a 10mm drill bit, drill into the stud where the markings are.




Hardware Contents


DESCRIPTION QUANTITY PART AA **Anchoring** 4pcs


4pcs BB Screw

BB AA


2) Push anchors provided into the newly drilled holes







4) Prior to hooking the mirror onto the wall, pull the power cord into the outlet, if your outlet is behind the mirror



5) Line the holes of the mirror with the screws on the wall, gently push the mirror against the wall and lightly pull down to secure the mirror.




Figure 5