

## SPECIFICATION SHEET

### SUBJECT

Sentinel Full Cut-Off Wall Pack

### CUSTOMER PROJECT

Project: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Cat. No.: \_\_\_\_\_  
 Qty: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 EEL Rep: \_\_\_\_\_



Telephone: 905 415 8878 Fax Number: 905 415 8872 Toll Free Telephone: 855 415 8878 Toll Free Fax: 855 415 8872

### DESCRIPTION

The LED Wall Pack is IP65 rated (with the drain hole plugs on) and it is designed with cutoff angles that shines downward towards the ground. It is the perfect replacement for traditional outdoor wallpacks in carports, parking garage and loading areas.

### SPECIFICATION FEATURES

#### Construction

- Heavy duty die-cast aluminum housing
- Castings are sealed with a one-piece gasket to inhibit the entrance of external contaminants
- Module compartment is fully sealed to prevent module damage by water infiltration

#### Finish

- Bronze
- Polyester powder paint

#### Driver and Module Access

- Door is hinged on the side and swings out for easy access during installation and service.

#### Shielding

- PC (Polycarbonate) Refractor

#### Compliance

- IP65 (with drain hole plugs on)
- UL 1598 Wet Location
- DLC Premium
- Suitable for wet and damp locations
- LED driver is IP65 rated
- Dark Sky Compliant

#### Beam Angle:

- 120°

#### Mounting

- Designed for wall mounting >4 feet from the ground
- LED panels facing downwards
- A built-in level is located within the fixture to facilitate mounting adjustments
- Built-in level to facilitate mounting adjustments
- Fixture Weight:  
 40W = 4.13lbs/1.87kg  
 60W = 4.38lbs/1.99kg

#### Warranty

- 5-Year Warranty (Standard)
- 10-Year Limited Warranty (Optional)



**LED  
SENTINEL WALL PACK**


## SENTINEL SERIES

### LED Full Cut-Off Wall Pack

Wattage(s)	40W, 60W
Voltage	120-347V
CCT	3000K, 4000K
Efficacy	130lm/W
Operating Temperature	-40°C to 45°C
CRI	70
Power Factor	>0.9
Total Harmonic Distortion	<20%
Surge Protection	4kV
Integral Photocell	120-277V
Dimming	1-10V



International Dark-Sky Association (IDA) Fixture Seal of Approval (FSA) is available for all products on this page utilizing 3000K color temperature and visor only.



WP4216 / WP4316 / WP4226 / WP4326

#### Dimensions















mm | 290(L) x 130(W) x 182(D)  
 inch | 11.4(L) x 5.12(W) x 7.17(D)



...continued

Telephone: 905 415 8878 Fax Number: 905 415 8872 Toll Free Telephone: 855 415 8878 Toll Free Fax: 855 415 8872

## ORDERING CODE, ENERGY AND PERFORMANCE DATA

Model No.	Delivered Lumens (lm)	Input Watts (W)	Voltage (V)	Colour Temp. (K)	Efficacy (lm/W)	Certification	Type
 <b>WP4216</b> 40W30K-120-347VNS1-10V	5400	40	120-347V	3000K	138	  	Standard
 <b>WP4316</b> 60W30K-120-347VNS1-10V	7800	60	120-347V	3000K	132	  	Standard
 <b>WP4226</b> 40W40K-120-347VNS1-10V	5445	39	120-347V	4000K	139	 	Standard
 <b>WP4326</b> 60W40K-120-347VNS1-10V	7880	59	120-347V	4000K	134	 	Standard




### NOTE:

- Lumens are estimated
- DLC qualified may not apply to all versions within a model. Please check the DLC Qualified Products List at [www.designlights.org](http://www.designlights.org) to confirm which versions are qualified.

### OPTIONAL ACCESSORIES

SPC1032 | Photo Cell for Wall Pack (120-277Vac)

WP4000V01 | WP4000 Visor 01 (Wall Pack Full Cut off)




...continued

Telephone: 905 415 8878 Fax Number: 905 415 8872 Toll Free Telephone: 855 415 8878 Toll Free Fax: 855 415 8872

## PHOTOMETRICS

### WP4216 / WP4226

40W30K-120-347VNS1-10V / 40W40K-120-347VNS1-10V




### Zonal Lumen Summary

Zone	Lumens	% Lamp	% Luminaire
0-30	1,719.4	32.8%	32.8%
0-40	2,731.8	52.1%	52.1%
0-60	4,417.9	84.3%	84.3%
60-90	807.3	15.4%	15.4%
70-100	312.4	6%	6%
90-120	6.2	0.1%	0.1%
0-90	5,225.2	99.7%	99.7%
90-180	17.4	0.3%	0.3%
0-180	5,242.6	100%	100%

### WP4316 / WP4326

60W30K-120-347VNS1-10V / 60W40K-120-347VNS1-10V



### Zonal Lumen Summary

Zone	Lumens	% Lamp	% Luminaire
0-30	2,545.7	32.7%	32.7%
0-40	4,050.0	52.1%	52.1%
0-60	6,557.6	84.3%	84.3%
60-90	1,195.0	15.4%	15.4%
70-100	460.5	5.9%	5.9%
90-120	8.4	0.1%	0.1%
0-90	7,752.6	99.7%	99.7%
90-180	24.2	0.3%	0.3%
0-180	7,776.8	100%	100%