





Industrial Grade

Maintained and Momentary Contact Extra Heavy-Duty  
Specification Grade Toggle Switches

Specifications and Features

- Positive switching action with center-off position
- Large silver cadmium-oxide contacts for long life, prevent sticking, welding and excessive pitting
- Clamp-type terminals accept up to #10 CU wire
- Full rated current capacity on fluorescent, tungsten and resistive loads; motor load capacity up to 80% switch current rating
- Backed by a Limited Ten-Year Warranty



BACK AND SIDE WIRED - MAINTAINED CONTACT U S

| Description                           | Color | Cat No.    |         |         |
|---------------------------------------|-------|------------|---------|---------|
|                                       |       | 120/277VAC |         |         |
| Rating                                |       | 15A        | 20A     | 30A     |
| Single Pole, Double Throw, Center Off | White | 1281-W     | 1285-W  | —       |
|                                       | Ivory | 1281-I     | 1285-I  | 1287-I  |
|                                       | Grey  | —          | 1285-GY | —       |
|                                       | Brown | 1281       | 1285    | 1287    |
|                                       | Red   | —          | 1285-R  | —       |
| Single Pole, Double Throw, Locking†   | Black | 1281-L     | 1285-L  | 1287-L  |
| Single Pole, Double Throw, Center Off | White | 1282-W     | 1286-W  | 1288-W  |
|                                       | Ivory | 1282-I     | 1286-I  | 1288-I  |
|                                       | Brown | 1282       | 1286    | 1288    |
| Double Pole, Double Throw, Locking†   | Ivory | —          | —       | 1288-LI |
|                                       | Black | —          | —       | 1288-L  |

†Key for Locking Switch: Cat. No. 55500-PRT.

BACK AND SIDE WIRED - MOMENTARY CONTACT U S

| Description                                     | Color | Cat No.    |         |       |
|-------------------------------------------------|-------|------------|---------|-------|
|                                                 |       | 120/277VAC |         |       |
| Rating                                          |       | 15A        | 20A     | 30A   |
| Single Pole, Double Throw, Center Off           | White | 1256-W     | —       | —     |
|                                                 | Ivory | 1256-I     | 1257-I  | —     |
|                                                 | Grey  | 1256-GY    | —       | —     |
|                                                 | Brown | 1256       | 1257    | 1260* |
|                                                 | Red   | —          | 1257-R  | —     |
| Single Pole, Double Throw, Center Off, Locking† | Ivory | —          | 1257-LI | —     |
| Single Pole, Double Throw, Center Off           | Brown | —          | 1257-L  | —     |
|                                                 | Brown | —          | —       | 1262* |

†Key for Locking Switch: Cat. No. 55500-PRT.  
CSA Certified except where indicated by\*.