

Type IC, Wet & Air-Tight

## **DESCRIPTION**

4" Round Regressed Gimbal LED With Integral Driver In Connection Box Unique & Patented Design: Gimbal Yet Air-Tight Without Housing Needed


#### **FEATURES & BENEFITS**

3" Deep - Install Where Ceiling Space Is Limited Type IC Rated - No Housing Required Fast & Easy To Install - Save On Labor Directional Beam - Great for Sloped Ceilings and Artwork CRI 90+ for True Color Rendering

### **MOUNTING**

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. Ceiling Clearance Required: 3"

# DIMENSIONS: ID 4 3/4" OD 5 3/4" Cut Out 4 3/4" to 5"



120V TRIAC Dimmable Driver Included



Optional 120V-347V Driver 0-10V Dimmable



Order Separately as Cat # LLL-LD1025T

# ORDERING GUIDE Example: LRG4 - 30K - WH

	CCT	Trim Finish	
LRG4	-	-	
2700K	27K	WH	White
3000K	30K	BK	Black
4000K	40K		
Dim to Warm	32K	White Trim Only In Stock	
3000K to 2000	OΚ		

# 4" Round Regressed Gimbal LED 11.4 W

Project:		
Location:		
Cat #:	Qty:	
Notes:		

SPECIFICATION				
Applications	Sloped Ceilings, Highlighting Artwork			
Energy Used	11.4 W			
Color Temperature	2700   3000   4000   [	DTW 30-20		
Light Output	960   1000   1050	800		
Halogen Equivalent	50 W			
Beam Angle	38° wide beam with 20° tilt and 360° rotatio			
CRI	90 +			
Default Driver Input	120V AC Tria	ac Dimmable		
Optional Driver Input	120V-347V AC 0-1	10V Dimmable		
Power Factor	0.95			
Approved Location	Insulated Ceiling & Wet Locations			
IP Rating	IP 54			
Air Tight	Yes			
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)			
Projected Life	70% Light Output at 50,000 Hours			
Certification	cULus, Energy Star (except DTW), T24			
Warranty	10 Year on Residential			
vvarianty	5 Year on Commercial Applications			

## **AVAILABLE TRIMS**






White

Black

## **ACCESSORIES**





Low Volage Extension Cables 6ft - cat #EXC6, 20ft - cat #EXC20 Max 40 ft Allowed. FT4 / CMR rated



Flat Rough-In Plates - cat #RIP5



Flanged Rough-In Plate - cat #FRP5

# **COMPLIANCE**









Type IC Air-Tight

USA Patent # US 10,344,952 B2 | Canada Patent # 2,967,954

**Lotus LED Lights USA** 

www.LotusLEDLights.com

**Lotus LED Lights CANADA** 

250 H Street # 301, Blaine WA 98230 tel 360-200-5500 Warehouses: Hainesport NJ, Naples FL, Dallas TX, Las Vegas NV, Lynnwood WA

800-15355 24 Ave Box 200, Surrey BC V4A 2H9 tel 604-538-3090