



4" Round Original Super Thin Recessed LED 9W

LY4RCS



Location:	
Cat #:	Qty:
Notes:	

SPECIFICATION				
Applications	Recessed Ceiling, Showers & Soffits			
Energy Used	9 W			
Colour Temperature	3000	4100		
Light Output	550	600		
Halogen Equivalent	50 W			
Beam Angle	110°			
CRI	80			
Default Driver Input	120V AC	Triac Dimmable		
Optional Driver Input	120V-347V AC	0-10V Dimmable		
Power Factor	0.95			
Approved Location	Insulated Ceiling, Wet & Damp Locations			
IP Rating	IP 54			
Air Tight	Yes			
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)			
Projected Life	70% Light Output at 50,000 Hours			
Certification	cULus, Energy Star			
Morront	10 Year on Residential			
Warranty	5 Year on Commercial Applications			

ACCESSORIES

Sold Separately



Low Volage Extension Cables 6ft - cat #EXC6, 20ft - cat #EXC20 Max 40 ft Allowed. FT4 / CMR rated



Flat Rough-In Plates - cat #RIP4



Flanged Rough-In Plate - cat #FRP4



Goof Ring OD 5 3/4" White cat #GR4 Black cat #GR4-BK

Type IC, Wet & Air-Tight

DESCRIPTION

4" Round Recessed LED With Integral Driver In Connection Box Fits Where No Other Recessed Fixture Can


FEATURES & BENEFITS

1/2" Deep - Install Directly Under Joists -Maximum Layout Flexibility Driver Inside Connection Box - No Junction Box Needed Fast & Easy To Install - Save On Labor Type IC Rated - No Housing Required

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. Ceiling Clearance Required For Driver: 2"

DIMENSIONS: ID 4 1/8" OD 4 3/4" Cut Out 4 1/8" to 4 1/4"



120V TRIAC Dimmable

Driver Included

Optional 120V - 347V

Driver 0-10V Dimmable





Order Separately as Cat # LLL-LD1535T

AVAILABLE TRIMS







ORDERING GUIDE Example: LY4RCS / 30K / WH

	CCT	Trim Finish	
LY4RCS	1	1	
3000K	30K	WH	White
4100K	41K	BK	Black
		BN	Brushed Nickel









Type IC Air-Tight