



Shown actual size: Maestro dimmer and 1-gang Claro wallplate in White (WH).

Control types

-  Single-pole (one location)
-  3-way (2 locations)
-  Multi-location (up to 10 locations)

Product family features

- True multi-location dimming from every location
- Tap on to preset level; tap off; tap twice for full on; touch rocker to adjust light level
- LEDs indicate light level and glow softly in the dark
- Delayed off provides light as you exit the room
- Line frequency compensation maintains stable light levels despite power line frequency and voltage variations
- Programming allows customized functions
- **C•L®, eco-dim and eco-timer models available**
- Coordinating Claro®, Satin Colors®, and Stainless Steel wallplates only available separately
- Custom engraving available for wallplates; see p. 237

Direct load type compatibility

-  Incandescent/halogen lighting
-  Dimmable CFL/LED lighting (screw-base)
-  Magnetic low-voltage lighting
-  Electronic low-voltage lighting
-  Fluorescent lighting
-  LED lighting
-  Switched lighting/fan/motor
-  Ceiling fans
-  Ceiling fan/lights

Load type requiring load interface

-  Neon/cold cathode lighting

Lighting load interfaces may be applicable for some load type, voltage, and capacity combinations. For additional information, see pp. 255–259.

Available finishes

Use **BOLD** color code in model number (Example: MA-600-**BR**)

Gloss finishes*



WH
White



LA
Light Almond



AL
Almond



IV
Ivory



GR
Gray



BR
Brown



BL
Black

Satin Colors® finishes*



SW
Snow



LS
Limestone



BI
Biscuit



ES
Eggshell



PD
Palladium



TP
Taupe



ST
Stone



BG
Bluestone



PL
Plum



SG
Sea Glass



TQ
Turquoise



GS
Goldstone



DS
Desert Stone



GB
Greenbriar

Metal finish wallplate**



MS
Mocha Stone



TC
Terracotta



SI
Sienna



HT
Hot



MR
Merlot



MN
Midnight



SS
Stainless Steel

* Coordinating wallplates only available separately. For wallplate information, see p.236.

** Stainless Steel wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) or Midnight (MN) controls. For wallplate information, see p.236.

Electronic low-voltage dimmers

Digital fade dimmers^{*,**}

Multi-location/single-pole 120V 600W	MAELV-600- XX ²
Multi-location/single-pole 120V 600W	MSCELV-600M- XX ³

3-wire fluorescent ballast/LED driver dimmers

Digital fade dimmers^{*}

Multi-location/single-pole 120V 6A	MAF-6AM- XX ¹
Multi-location/single-pole 120V 6A	MSCF-6AM- XX ²
Multi-location/single-pole 277V 6A	MAF-6AM-277- XX ¹
Multi-location/single-pole 277V 6A	MSCF-6AM-277- XX ²

For use with Hi-lume® 3D and EcoSystem® ballasts, and Hi-lume 1%, and Hi-lume Premier 0.1% LED drivers

For more information on Hi-lume 1% LED drivers, visit www.lutron.com/HilumeLED.

No derating required if ganged.

Adjustable low-end trim.

Electronic switches



- For multi-location switching, use one Maestro multi-location switch with Maestro companion switches
- Tap switch on/off

Switches

Electronic switches^{*}

Multi-location/single-pole 120V 8A light 3A fan	MA-S8AM- XX ¹
Multi-location/single-pole 120V 8A light 3A fan	MSC-S8AM- XX ²
Multi-location/single-pole 277V 6A light	MAF-S6AM-277- XX ¹
Multi-location/single-pole 277V 6A light	MSCF-S6AM-277- XX ²

8A rated for: incandescent/halogen, magnetic low-voltage, electronic low-voltage, fluorescents, CFLs, LEDs, and general purpose fans.

6A rated for: incandescent/halogen, magnetic low-voltage, electronic low-voltage, fluorescents, CFLs, and LEDs.

XX¹: Gloss colors codes, see p. 57

XX²: Satin Colors® codes, see p. 57

Wallplates not included. Order separately, see p. 236

All models must be derated if ganged unless otherwise noted, see pp. 250–252.

^{*} **Requires neutral wire connection**

^{**} Minimum load required, see specification submittal