

PROJECT NAME: _____ CAT. #: _____
 NOTES: _____ FIXTURE SCHEDULE: _____

Adjustable Residential Retrofit Downlight

RR Series



Description:

Constructed with a high-efficacy LED array, the Downlight Residential Retrofit series features an optical diffuser that produces high lumen transmission and even illumination. The fixtures are suitable for wet locations; available in 90 CRI with CCT selectability that includes 2700K/3000K/3500K/4000K/5000K.

Features:

- 2700K/3000K/3500K/4000K/5000K CCT selectable
- Adjustable up to 30°
- Beam Angle: 95°
- High CRI: ≥ 90
- Toolless installation

Dimming:

- 120V option available with 120V triac dimming (10%)

Mounting:

- RRA4 model fits into 4" housings
- RRA6 model fits into 5" and 6" housings
- E26 screw-base connector included

Construction:

- Stamped steel aluminum
- Plastic lens

Listings:

- ETL listed for Wet Locations, Indoor
- ENERGY STAR Certified
- Supports T24 Part 6 high efficacy lighting requirements

Ordering Information

FAMILY	SIZE	WATTAGE	VOLTAGE	CRI	CCT	FINISH
RRA= Adjustable Retrofit Downlight	6= 5" 6"	10= 10W	[BLANK]= 120V, Triac Dimming	9= 90 CRI	CS= 2700K/3000K/3500K/4000K/5000K CCT Selectable	W= White

Stocked Items

MODEL NUMBER	ORDER CODE	DESCRIPTION	ENERGY STAR #
RRA6109CSW	105652	Adjustable Residential Retrofit Downlight, 6", 10W, 2700K/3000K/3500K/4000K/5000K CCT Selectable	2372484



5-year standard warranty (further details available at www.maxlite.com/warranties)

Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

Adjustable Residential Retrofit Downlight

RR Series

Compatible Dimmers

MANUFACTURER	DIMMER MODEL
Lutron	MACL-153M
	SCL-153P
	DVCL-153P
	CTCL-153PDH-WH
	TGCL-153PH-WH
	DVWCL-153PH-WH

Specifications

	RRA6109CSW
Power Consumption	10W
Lumens Delivered	900 lm
Efficacy	90 lm/W
Equivalency	75W INC
CRI	≥ 90
Color Temperature (K)	2700K, 3000K, 3500K, 4000K, 5000K
L70 Lumen maintenance	≥ 50,000
Power Factor	≥0.9
Input Voltage	120V
Operating Temperature	-4°F to 104°F
Housing	Stamped Aluminum
Lens	Plastic
Mounting	Retrofits into 5" and 6" housings
Listings	Energy Star, JA8, T20, cETLus, RoHS, FCC
Environment	Wet locations, Indoor Only
Warranty	5 Years

Dimensions

