

Date:	Project Name:	
Туре:	Part Number:	







ORION SERIES **LED UFO HIGHBAY**

DESCRIPTION

Our new generation LED highbays are ideal for replacing HID High Bay fixtures, offering high performance and long life. Designed precision spherical and convex lens and offers low brightness, uniform illumination and high efficiency LED platform. Designed with easy installation of sensors at the face of the fixture.

FEATURES

- **DLC Premium**
- Excellent heat dissipation.
- 0-10V Dimming
- **NSF** Compliant
- Mounting options: hook/chain, pole pendent and surface mounting
- Operating temperature: 4°F to +122°F (-20°C to +50°C)
- Dual Voltage 120-347V
- Suitable for wet locations IP65 rated
- Polycarbonate Lens
- Multi Wattage & 150 lm/w
- White Finish
- Includes 6' cord, ring bolt mounting accessory & safety hanging kit
- 5 year warranty

APPLICATIONS



Commercial Building



Industrial/Warehouse



Retail Facility



























Date:	Project Name:
Туре:	Part Number:

SPECIFICATION

ORDER#	MODEL#	WATTS	VOLTAGE (V)	LUMENS	BEAM ANGLE	DIMMABLE	CCT (K)
R34223	RENO-HBU-150W-DV-MCCT-R1-ECO	100/125/150W	120-347V	14,800/18,500/ 22,200 lm	90°	0-10V	35/40/50K
R34224	RENO-HBU-240W-DV-MCCT-R2-ECO	150/200/240W	120-347V	23,200/29,600/ 35,520 lm	90°	0-10V	35/40/50K

ACCESSORIES

ORDER#	MODEL#	DESCRIPTION
R83005	RENO-EM-40RM	Emergency LED Driver

SENSOR OPTIONS

ORDER#	MODEL#	DESCRIPTION
R71002	RENO-SENSOR-MW-H	Dimming Microwave Sensor

REMOTE OPTIONS

ORDER#	MODEL#	DESCRIPTION
R73002	RENO-REMOTE-H	Controller for Bi-Level Sensor






Date:	Project Name:
Туре:	Part Number:


DIMENSIONS

Rings:






116,8(4.6")



160,6(6.3")



Ø 325,7(12.8")