

LED 4-PIN & 2-PIN PL BULB



APPLICATIONS

- General Lighting
- Recessed Down Lights
- Display Cases
- Damp Location Installation

FEATURES

- Replacement for Conventional 9W, 13W, 18W, 26W, and 42W PL Lamps
- Directly Compatible with Most Existing CFL Ballasts(4-Pin & 2-Pin)
- Line Voltage(120-277V)/Bypass ballast(2-Pin Only)
- Suitable for use in enclosed fixture
- Suitable for use in dry and damp locations
- Operating Temperature: -20°C/-4°F to 45°C/113°F
- 50,000+ Hour Lifetime(L70)
- 4 PIN MCCT SWITCH



SPECIFICATION

ORDER #	MODEL#	BASE TYPE	LUMENS OUTPUT	BEAM ANGLE	WATTS	INPUT VOLTAGE	CCT	CRI	DLC
R24001	WLL-LED6/2P/H/835	GX23	550lm	120°	6W	120-277V/BF	3500K	83+	NO
R24009	WLL-LED6/2P/MCCT	GX23	550lm	120°	6W	120-277V	2700/3000/ 3500/4000/5000K	83+	NO
R24007	WLL-LED11/4P/H/MCCT	G24Q	1100lm	120°	11W	BF	3000/3500/4000K	83+	YES
R24008	WLL-LED11/4P/V/MCCT	G24Q	1100lm	120°	11W	BF	3000/3500/4000K	83+	YES

DIMENSION

