



# S29907

17T8/LED/48-850/BP 120-277V  
17 watt T8 LED; 5000K; Medium Bi Pin base; 50000 Average  
rated hours; 2200 Lumens

## Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage\*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29907

\*Existing wiring to both sockets can remain in place

\*Will work on both shunted or non-shunted sockets

| Item Number | UPC          | Voltage | Watts | Operating Frequency | Fluorescent Equivalent | Lamp Shape | Base          |
|-------------|--------------|---------|-------|---------------------|------------------------|------------|---------------|
| S29907      | 045923299070 | 120-277 | 17    | 50/60Hz             | 32W                    | T8         | Medium Bi-Pin |

| ANSI Base | Lamp Code                   | Dimmable/Non-Dimmable | Finish | MOL In Inches | MOD In Inches | Initial Lumens | Average Rated Hours |
|-----------|-----------------------------|-----------------------|--------|---------------|---------------|----------------|---------------------|
| G13       | 17T8/LED/48-850/BP 120-277V | Non-Dimmable          | White  | 48"           | 1.00"         | 2200           | 50000               |

| Kelvin Temp | Color         | CRI | Beam Spread Deg | Operating Temperature                   | Pack | CEC Status                    | DLC ID:                                    |
|-------------|---------------|-----|-----------------|-----------------------------------------|------|-------------------------------|--------------------------------------------|
| 5000        | Natural Light | 82  | 210             | -20C (-4F) to a maximum of +45C (+113F) | 25   | Lawful for sale in California | PL61R5NR5TT1<br><a href="#">DLC Search</a> |

| RoHS Compliant | UL or ETL Listed | UL Classification                      | Warranty                       |
|----------------|------------------|----------------------------------------|--------------------------------|
| Yes            | Yes              | cULus Classified - Damp Location Rated | <a href="#">5 Year Limited</a> |



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051