



# Microwave Sensor for Select Series UFO

## Product Specifications



HM1 is an innovative motion detector that uses 5.8GHz high frequency that can detect motion through plastic, glass and thin non-metal materials.

The sensor supplies a simple energy-saving solution to use light only when and where you need it. It automatically switches on/off light based on motion and ambient light level. Easily install the HM1 in the pre-installed Zhaga Book-18 socket on the Select Series UFO.

### Reasons to choose the HM1 Motion Sensor from TCP


- Automatic switching based on motion and light level
- Zero-crossing point operation helps protect the sensor against in-rush current
- Zhaga Book-18 Receptacle for easy twist-lock installation
- Detection area, time delay and daylight threshold can be precisely set via remote control  
\*remote sold separately
- Wide detection area, range up to 16m in diameter
- 5.8GHz microwave module provides detection for mounting heights up to 15m

### Ideal Applications


- Warehouses
- Storage
- Manufacturing Facilities

## Specifications

Operating voltage	120-277Vac, 50/60Hz
HF system	5.8GHz $\pm$ 7.5MHz, ISM wave band
Power consumption	$\leq$ 0.3mW (Standby)
Detection zone	Max.(D x H): 16m x 15m
Detection sensitivity	25% / 50% / 75% / 100%
Hold time	5s / 30s / 1min / 3min / 20min / 30min
Daylight sensor	2 Lux / 10 Lux / 30 Lux / 50 Lux / 80 Lux / 120 Lux / Disable
Mounting height	15m Max.
Motion detection	0.5-1ms
Detection angle	150°(wall installation) 360°(ceiling installation)
Operating temperature	-20°C to 60°C
IP rating	IP65



## Detection Pattern


















## Factory Settings

- Detection area 100%
- Hold time 5s
- Daylight threshold disabled
- Standby period 0s
- Standby dimming level 10%

\*Can be customized via remote

## Remote Instructions



Buttons	Function	Performance
	ON/OFF	Turn ON or OFF the sensor.
	MW/PIR	Switch from Microwave to PIR Detection (In applicable sensors).
	Reset	Press it to start detection programming; before pressing any other buttons, the screen shows default programming (Detection Area 100%, Hold time 5S, Daylight Disable, standby Dimming 10%, Standby Period 0S).
	Start	Press it before using the memory function; the S will start blinking which signifies that the changes made will be stored in the memory.
	Memory	Press it after the desired functions have been selected; the S will become a solid M which signifies that the changes have been saved.
	Apply	Press it to deliver the preset program to the specific sensors; every press will make the whole screen blink gently.
	Detection Area	Also known as "sensitivity", 100% means the highest sensitivity and longest distance. Press it, the sensitivity icon will blink and press the +/- buttons to adjust.
	Hold Time	The period that light will stay illuminated 100% after no motion is detected. Press it, the clock icon will blink and press the +/- buttons to adjust.
	Daylight Threshold	The preset lux level to compare with ambient brightness when motion gets detected. Press it, the sun icon will blink and press the +/- buttons to adjust.
	Standby Period	The period after hold time during which light keeps standby dimming level. Press it, the sun clock icon (with arrow) will blink and press the +/- buttons to adjust.
	Standby Dimming Level	After hold time the light will dim from 100% to optional standby dimming levels. Press it, the light bulb icon will blink and press +/- buttons to adjust.
	UP	The main functional buttons to adjust the factors to wanted level.
	DOWN	
	POWER	Supports to manually change dimming output detection mode. Press it, the light power icon will blink and press +/- buttons to adjust.
	Test Mode	Supports to check if the sensor works correctly with a short 2S hold time. Press it and hold time will change to 2S, and the changes will not be saved.

## Remote Instructions

---

### Basic On/Off Mode:

1. Press the power button (Device will power off, press again to turn on).
2. The Sensor will be turned off and the fixture will be in basic on/off mode.
3. To dim the fixture, press the up and down arrows.

### Sensor Mode:

1. Press the Scene button to enable the sensor  
(Device will dim down and up to signify the signal has been received).
2. The sensor will use the settings currently displayed on the remote.

### To Program the Remote and Fixture:

1. Press the start button to set the remote into programming mode  
(The S icon will flash in the bottom left of the screen).
2. Press the individual setting buttons and use the up and down arrows to select the setting  
(the individual setting icons will flash on screen when selected).
3. After selecting all the desired settings, press the memory button to save the settings to the remote.
4. Aim the remote at each device you would like to program and press apply  
(The device will dim down and up to signify the signal has been received).

# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcpi.com](http://tcpi.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516