



VIV-PAR20/I90

Features & Benefits

Deliver nearly perfect color accuracy and reproduction
High CRI (90+), Dimmable

7W replaces 50W incandescent

25,000 hour average life

Enclosed luminaires application

Wet location approved


Warranty & Cautions

3-year limited warranty from the date of purchase

Operating temperature range between -40°C and +45°C

cETL listed, FCC compliant, RoHS compliant

Dimensional drawing



Product Specification

Ordering Code	Model Number	Watts	Replacement Incandescent	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Enclosed Fixture	Wet Location	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
1752104	VIV-PAR20/I90/7W/27/WFL40/D	7	50W	E26	120	25,000	40°	500	2700	90	Y	Y	2.47	3.46	50
1752211	VIV-PAR20/I90/7W/30/WFL40/D	7	50W	E26	120	25,000	40°	500	3000	90	Y	Y	2.47	3.46	50
1752409	VIV-PAR20/I90/7W/40/WFL40/D	7	50W	E26	120	25,000	40°	500	4000	90	Y	Y	2.47	3.46	50
1752506	VIV-PAR20/I90/7W/50/WFL40/D	7	50W	E26	120	25,000	40°	500	5000	90	Y	Y	2.47	3.46	50

Ordering Information

Example: VIV-PAR20/I90/7W/27/WFL40/D

LED CLASS	LAMP TYPE	CRI	WATTAGE	CCT (K)	BEAM ANGLE	DIMMABLE
VIV (Vivid)	PAR20	I90 (CRI≥90)	7W	27 (2700K) 30 (3000K) 40 (4000K) 50 (5000K)	WFL40 (40°)	D (dimmable)